



# Ordering information

## Fuse links, DIN-type, gG

### HRC fuse links, gG, general application OFAF\_H\_, \_<500V




OFAF000H\_



OFAF00H\_



OFAF0H\_



OFAF1H\_

NH-size	Rated voltage AC / DC	Rated current	Power loss	Type code	Order code	Delivery batch	Weight
		In A	Ph W			pcs	kg
000	500V / 250V	2	1.9	OFAF000H2	1SCA022627R0230	9	0.12
		4	1.5	OFAF000H4	1SCA022627R0310	9	0.12
		6	1.6	OFAF000H6	1SCA022627R0400	9	0.12
		10	1.1	OFAF000H10	1SCA022627R0580	9	0.12
		16	1.8	OFAF000H16	1SCA022627R0660	9	0.12
		20	2.3	OFAF000H20	1SCA022627R0740	9	0.12
		25	2.4	OFAF000H25	1SCA022627R0820	9	0.12
		32	3.1	OFAF000H32	1SCA022627R0910	9	0.12
		35	3.0	OFAF000H35	1SCA022627R1040	9	0.12
		40	3.7	OFAF000H40	1SCA022627R1120	9	0.12
		50	4.1	OFAF000H50	1SCA022627R1210	9	0.12
		63	5.4	OFAF000H63	1SCA022627R1390	9	0.12
		80	6.5	OFAF000H80	1SCA022627R1470	9	0.12
		100	7.5	OFAF000H100	1SCA022627R1550	9	0.12
00	500V / 250V	125	10	OFAF00H125	1SCA022627R1630	3	0.18
		160	11.3	OFAF00H160	1SCA022627R1710	3	0.18
0	500V / 250V	6	1.6	OFAF0H6	1SCA022627R1800	3	0.21
		10	1.1	OFAF0H10	1SCA022627R1980	3	0.21
		16	1.8	OFAF0H16	1SCA022627R2010	3	0.21
		20	2.3	OFAF0H20	1SCA022627R2100	3	0.21
		25	2.4	OFAF0H25	1SCA022627R2280	3	0.21
		32	3.1	OFAF0H32	1SCA022627R2360	3	0.21
		35	3.0	OFAF0H35	1SCA022627R2440	3	0.21
		40	3.7	OFAF0H40	1SCA022627R2520	3	0.21
		50	4.1	OFAF0H50	1SCA022627R2610	3	0.21
		63	6.6	OFAF0H63	1SCA022627R2790	3	0.21
		80	8.0	OFAF0H80	1SCA022627R2870	3	0.21
		100	9.4	OFAF0H100	1SCA022627R2950	3	0.21
		125	11.8	OFAF0H125	1SCA022627R3090	3	0.21
		160	14.6	OFAF0H160	1SCA022627R3170	3	0.21
		200	18.1	OFAF0H200	1SCA022629R5140	3	0.30
		224	19.2	OFAF0H224	1SCA022629R5220	3	0.30
		250	20.3	OFAF0H250	1SCA022629R5310	3	0.30
1	500V / 250V	16	1.8	OFAF1H16	1SCA022627R3250	3	0.28
		20	2.3	OFAF1H20	1SCA022627R3330	3	0.28
		25	2.4	OFAF1H25	1SCA022627R3410	3	0.28
		32	3.1	OFAF1H32	1SCA022627R3500	3	0.28
		35	3.0	OFAF1H35	1SCA022627R3680	3	0.28
		40	3.7	OFAF1H40	1SCA022627R3760	3	0.28
		50	4.1	OFAF1H50	1SCA022627R3840	3	0.28
		63	6.6	OFAF1H63	1SCA022627R3920	3	0.28
		80	8.0	OFAF1H80	1SCA022627R4060	3	0.28
		100	9.4	OFAF1H100	1SCA022627R4140	3	0.28
		125	11.8	OFAF1H125	1SCA022627R4220	3	0.40
		160	14.6	OFAF1H160	1SCA022627R4310	3	0.40
		200	18.0	OFAF1H200	1SCA022627R4490	3	0.40
		224	19.0	OFAF1H224	1SCA022627R4570	3	0.40
		250	20.0	OFAF1H250	1SCA022627R4650	3	0.40
		315	20.5	OFAF1H315	1SCA022627R4730	3	0.40
		355	23.7	OFAF1H355	1SCA022701R4520	3	0.40