



Fuse-link, 700 A, AC 690 V, size 3, 76 x 90 x 141 mm, aR, IEC, single indicator

Part no. **FUSE 700A 690V 3STN/110 AR**
 Catalog No. **170M6035**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Rated current	I	A	700
Rated voltage			AC 690 V
Construction size			size 3
Size			76 x 90 x 141 mm
Utilization category			aR
Status indicator			single indicator
usable for size/applications			semiconductor protection
Standard/Approval			IEC
Shape			square body with centre-bolted tags (slotted)
Standards/Regulations			IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			3
Type of current			AC
Rated voltage AC		V	690
Rated voltage DC		V	
Rated current		A	700
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	
Colour code			None
Type of fuse status indicator			Top fuse status indicator
Power loss at rated current		W	
Mounting holes			M10
Centre-to-centre distance of connections		mm	108