



Fuse-link, 200 A, AC 1250 V, 100 kA, size 1, 53 x 63 x 135 mm, aR, IEC, type T indicator, live gripping lugs



Part no. FUSE 200A 1250V 1SHT AR CU
 Catalog No. 170M4700

Delivery program

| | | | |
|------------------------------|---|----|--|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Rated current | I | A | 200 |
| Rated voltage | | | AC 1250 V |
| Construction size | | | size 1 |
| Size | | | 53 x 63 x 135 mm |
| Utilization category | | | aR |
| Status indicator | | | type T indicator |
| Description | | | live gripping lugs |
| Breaking Capacity | | kA | 100 |
| usable for size/applications | | | semiconductor protection |
| Standard/Approval | | | IEC |
| Shape | | | square body with special bladed contacts |
| Standards/Regulations | | | IEC 60269-4 |

Technical data ETIM 7.0

| | | | |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) | | | |
| Construction size | | | Other |
| Rated current | | A | 200 |
| Rated voltage | | V | 1250 |
| Voltage type | | | AC |
| Rated switching capacity | | kA | 100 |
| Utilization category | | | aR (accompanied semiconductor protection) |
| Type of fuse status indicator | | | Top fuse status indicator |
| Insulated metal gripping lugs (IMGL) | | | No |