



Fuse-link, high speed, 800 A, AC 1000 V, DIN 3, 90 x 75 x 150 mm, aR, DIN, IEC, single indicator, live gripping lugs



Part no. **FUSE 800A 1000V DIN 3 AR UR**
 Catalog No. **170M8647**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	800
Rated voltage			AC 1000 V
Construction size			DIN 3
Size			90 x 75 x 150 mm
Utilization category			aR
Status indicator			single indicator
Description			live gripping lugs
usable for size/applications			Protection of power rectifiers
Standard/Approval			DIN IEC
Shape			square body with knife blade contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Knife blade fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			EV000154
Rated current		A	800
Rated voltage			1000
Voltage type			AC
Rated switching capacity		kA	100
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Top fuse status indicator
Insulated metal gripping lugs (IMGL)			No