



Cart 中文

Home About Us News Products Certificate Services Contact

MIN ING

Professional manufacturer for High & Low Voltage Fuses and Fusegears Combined Electrical Appliance

# Product Center

>> Home / Product Center / gPV FUSE



Parameter Feature Outline Curve

### PV fuses: PV10

No.	Rated voltage (V)	Rated current (A)	70%In Power consumption = (W)	100%In Power consumption = (W)	Breaking capacity	The minimum packing(Only)	Each Box(Only)
1	DC 1000	2	0.62	1.75	DC1000V/10kA	10	
2		3	0.75	2.10			
3		4	0.51	1.20			
4		5	0.62	1.40			
5		6	0.65	1.50			
6		8	0.72	1.73			
7		10	0.85	1.94			
8		12	1.10	2.56			
9		15	1.70	3.15			
10		20	1.72	3.28			
11		25	2.85	4.32			
12		30	3.20	5.30			

To obtain the use of categories and certification

gPV    



**INQUIRY**  
400-800-9662

#### About Mingrong

- Company Profile
- Development
- Organization
- President address

#### News and media

- Company news
- Enterprise video
- Exhibition information

#### Products and Services

- Fuse links
- Bole connected fuse links
- Fuse bases
- Fuse alarms
- Fuse carriers
- Combinating electric of fuse
- Automobile Fuse
- High voltage fuse

#### Support

- Customer Service Center
- Customer complaints
- Marketing network
- Technical FAQ
- Download

#### Jobs

- Talent concept
- Recruitment information
- Recruitment line

#### Contact Us

- Regions
- Contact
- Sitemap

