

# DATASHEET - RED SPOT 400A FRONT/BACK STUD CONNECTED



**Fuse holder, low voltage, 400 A, AC 690 V, BS88/B4, BS88/C1, 1P, BS, front/back stud connected, black**



Powering Business Worldwide™

**Part no. RED SPOT 400A FRONT/BACK STUD CONNECTED**  
**Catalog No. RS400PH**

## Delivery program

Product range			Fuse accessory
Basic function			Fuse-holder
Field of application			low voltage
Rated current	I	A	400
Rated voltage			AC 690 V
Construction size			BS88/B4 BS88/C1
Description			front/back stud connected black
Protection			IP20
Number of poles			1P
usable for size/applications			fuse-links TM, EE and P11-660
Standard/Approval			BS
Standards/Regulations			BS88-2 IEC 60269-2

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse base (EC000067)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Low-Voltage HRC fuse base (ecl@ss10.0.1-27-14-21-06 [AKE278013])			
Construction size			Other
Number of poles			1
Rated current		A	400
Bus-mounting type			No
Swivelling mechanism			No