



Cat. No.	Models	Rated voltage (V)	Rated current (A)	Dimensions/sizes (mm)								Weight (g)
				Fig.	A	B	C	ϕ D	E	F	ϕ d	
0601	RS94A	250	40~200	6.1	70	52	32	28	22	5	8.2 × 12	98
0602	RS94C	250	40~200	6.1	80	62	42	28	22	5	8.2 × 12	106
0603	RS94D	250	30~200	6.1	80	57	26	29	22	5	8.2 × 12	120
0604	RS94E	250	30~200	6.1	80	60	41	31	24	5	8.2 × 12	142
0605	RS94F	250	40~200	6.1	80	58	38	33	25	5	8.2 × 12	135
0606	RS94G	250	40~250	6.1	88	62	42	36	26	5	10.2 × 15	202.5
0607	RS94H	250	30~150	6.1	70	53	27	22	16	5	8.2 × 12	82
0608	RS94J	250	40~160	6.1	67	51	26	26	19	3.5	8.2 × 12	102
0609	RS95A	500/660	50~200	6.1	91	72	54	28	22	5	8.2 × 12	112.5
0610	RS95B	500/660	50~200	6.1	92	73	54	31	25	5	8.2 × 12	150
0611	RS95C	500/660	50~100	6.1	92	73	54	26	19	5	8.2 × 12	114