

Eaton 170M3422

Catalog Number: 170M3422

Eaton Bussmann series high speed square body fuse, 700V (UL), 690V (IEC), 550A, 200 kAIC, Top fuse status indicator, Fuse, Class aR, Flush - 170M3422

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M3422
	UPC
	051712256070
EAN	Product Length/Depth
5027590447690	155 mm
Product Height	Product Width
45 mm	90 mm
Product Weight	Warranty
245.3333333 g	Not Applicable
Compliances	Certifications
CE Marked RoHS Compliant	IEC Rated UL Recognized



Product specifications

Interrupt rating

200 kAIC

Center-to-center distance of connections

50 mm

Insulated metal gripping lugs (IMGL)

No

Current type

AC

Mounting method

Flush

Amperage Rating

550 A

Fuse type

Flush end

B/Visual indicator

Fuse size

1*

Voltage rating

690 V (IEC), 700 V (UL)

Fuse indicator

Top fuse status indicator

Construction size

Other

Clearing (I²T)

230000 at 660 V

Rated voltage AC

690 V

Color

None

Mounting dimension

M8

Utilization category

aR (accompanied semiconductor protection)

Watt losses

75 W

Resources

Catalogs

Product overview for machinery

Bussmann series complete full line catalog no. 1007

170M3422-Eaton Bussmann series high speed square body fuse

Compliance information

CE Fuse-links for the protection of semiconductor devices, sz1* up to 630A

UKCA Fuse-links for the protection of semiconductor devices, sz1* up to 630A

Specifications and datasheets

Eaton Specification Sheet - 170M3422

Type

Fuse

Fuse shape

Square body, flush end contacts

Breaking capacity

200 kA

Class

Class aR

Pre arc (I2T)

34000

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Voltage type

AC

Packaging type

Standard



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)