



Cart 中文

Home About Us News Products Certificate Services Contact

MIN ING

Professional manufacturer for High & Low Voltage Fuses and Fusegears Combined Electrical Appliance

Product Center

>> Home / Product Center / gPV FUSE

Parameter Feature Outline Curve

PV support pieces: PVH-30(X)



Type	Working voltage	Resistive current I _{th}	Rated power acceptance (W)	Use categories	Protection grade	Rated short-circuit current limitation
PVH-30	DC1000V	30A(max)	5.3(max)	DC-20B	IP20	DC1000V/10KA
PVH-30(X)						
Product packaging parameters	The minimum package: 12 / box FCL: 192 / box					
To obtain the use of categories and certification		gPV RoHS CCC CB CE				



浙江明融电器 中国制造商

INQUIRY
400-800-9662

About Mingrong

- Company Profile
- Development
- Organization
- President address

News and media

- Company news
- Enterprise video
- Exhibition information

Products and Services

- Fuse links
- Bole connected fuse links
- Fuse bases
- Fuse alarms
- Fuse carriers
- Combinating electric of fuse
- Automobile Fuse
- High voltage fuse

Support

- Customer Service Center
- Customer complaints
- Marketing network
- Technical FAQ
- Download

Jobs

- Talent concept
- Recruitment information
- Recruitment line

Contact Us

- Regions
- Contact
- Sitemap

